



**NEO**  
**LEADER** Fan  
**EASY POW'AIR**  
TECHNOLOGY

---

**PETROL-DRIVEN  
FAN** **MT236**

---

**A very concentrated and ultra-powerful jet of air  
due to an optimal combination of:**

- A high-strength propeller matched to the power of the engine
- A red double-layer monobloc shroud made of reinforced high-density polyethylene
- A high-tech composite grille

**Positioning from 0.90 m to 6 m in front of a door  
without loss of power for:**

- More space to move about
- Less noise inside the building

**Automatic optimal +10° tilt**

- When handle raised

**Precise tilt adjustment from +10° to +20°**

- For optimization of direction of air stream up entrance steps

**Protective frame**

- With grey epoxy coating

**Stable & easy to handle**

- With large rear wheels

**Compact**

- For easy storage in vehicle trunks

**Integrated stabilizer prop at rear**

- Also enables fan to be tilted to -10° for downward ventilation

## MULTI-APPLICATION

- Indoor and outdoor: Protected against splashing water
- Alone, at the entrance of a building in VPP
- In VPP combined with other fans
- Blowing with ducts (optional)
- As a foam generator with its high expansion adapter (optional)
- As a misting device (option)

## CHARACTERISTICS

MT236 NEO	
Reference	I60.10.053N
Open air flow	52 550 m <sup>3</sup> /h
PPV air flow according to AMCA	33 660 m <sup>3</sup> /h
Weight	39,6 kg
Dimensions L x H x D	550 x 560 x 515 mm
Propeller diameter	420 mm
Run time at full speed	2h10
Engine	HONDA GX 160 engine (4-stroke) Automatic engine cutout if oil runs out. Assembly inspected and approved by Honda Motor Co., Ltd
Engine power	4.8 HP according to standard SAE J1349 of 2007
Noise level	93 dB at 3 m
Ventilation type	PPV blowing
Application	Single door, e.g. house, small apartment block
Garantees	5 years / 3 years

## OPTIONS - ACCESSORIES

CO-reducing LEADER Cat catalytic converter	Ref. I60.20.142
Mister without coupling	Ref. I60.20.104
High expansion foam adapter without coupling delivered with 35m of polyane plastic film duct	Ref. I60.20.105
Hour meter	Ref. I60.20.135
Exhaust adapter	Ref. I60.20.145
Exhaust extension (length: 2.5m)	Ref. I60.20.012
Protective cover	Ref. I60.20.017
5m ventilation duct	Ref. I60.20.152

## REDUCED COST OF OWNERSHIP

Very low maintenance due to the very robust design and materials used.

ZF.03.430.EN.1